



SHERPA HD MOLLE HEADREST COVER

USE OF SPACE ON HEADREST

INSTALLATION INSTRUCTIONS



To install the HD Molle Headrest Cover, remove the headrest from the seat by depressing the lock buttons on the top of the seat and pulling the headrest out of the seat. Wrap the cover around the headrest with the Molle straps in the back and the Overland Outfitters logo in the front. Pull the ends of the cover tightly around the headrest and close the Velcro, pushing the Velcro together tightly. Replace the headrest by inserting the headrest rods back into the sockets in the top of the seat.



SHERPA HD MOLLE HEADREST COVER

USE OF SPACE ON HEADREST

CARE INSTRUCTIONS



The HD Molle Headrest Cover is made from heavy cotton duck canvas fabric and is designed to give years of service on the road and trail. Canvas is very easy to clean and handle - a soft and dry bristled brush can be used to remove any loose dust or dirt.

If the canvas needs further cleaning, mix clean water and a small amount of mild detergent and use a damp towel or bristled brush dipped in the solution and scrub or rub the dirty areas gently. Lightly spray the canvas area with water to remove the soap residue and dry with a towel.

To keep the Headrest Cover looking new longer, and to prevent any fading in high-sunlight environments, we recommend either Gold Eagle 303 Aerospace Marine UV Protectant or Nikwax Tent & Gear SolarProof. Both come in an easy-to-use spray bottle and will protect from harmful UV rays and will also repel dust and dirt.

Note: Do not Dry-Clean, bleach or put in the dryer as these may potentially discolor the canvas.